

# Product Bulletin Imagine Glass™



## Product Description

Imagine Glass™ is a glass construction consisting of two lites of glass laminated together with a proprietary decorative interlayer. The resulting construction is certified safety glass. Annealed, heat strengthened and tempered glass can be used and any thickness is possible. Bent glass structures are also available. Almost any look is possible, including sandblast looks, logos, custom colors, geometric designs, textures, metallic looks and full color / continuous tone graphics.

## Design Elements

*Unlimited Design* – Virtually any design can be incorporated into the glass. Customers can send a file, use one of the existing designs in our idea gallery, or allow our graphic design experts to create a custom design for you.

*Color* – An almost unlimited color range is available, including custom and corporate colors and metallics. Multi-color images offer many interesting design options. Our technology offers special colors that can be utilized to create texture, color shift and other unique effects.

*Light Transmission Control* – The amount of light passing through Imagine Glass™ can be easily manipulated by adjusting the design and/or opacity of the image to create the right amount of shading for your environment.

*Image Detail* – Lines and image edges are sharp and detailed.

*Durability and Specifications* – Imagine Glass™ has an extremely long life, and can be used indoors or outdoors. Your product can be made with virtually any type of glass to create a certified safety glass.

*Exceptional UV Blocking* – Ultra violet degradation and fading of objects on the interior side of the glass is insignificant. The glass blocks 99.5% of solar radiation in the 380 nanometer wavelength and below. In contrast, ¼ inch clear float glass *transmits* over 70% of the same solar radiation.

*Sound Deadening* – Sound attenuation is excellent and significantly surpasses that of monolithic glass.

*Penetration Resistance* – The imaged interlayer has been designed to add significant strength to the laminated glass construction, delivering exceptional penetration and impact resistance over and above standard safety glass.

### **Relevant Standards**

Imagine Glass™ is safety glass, which by definition is designed to minimize the likelihood of cutting or piercing injuries when broken. Imagine Glass™ complies with all major building codes and meets the following industry standards:

ANSI Z97.1-1984 (R1994) – American National Standard for Safety Glazing Materials Used in Buildings – Safety Performance Specifications and Methods of Test

CPSC 16 CFR 1201 Safety Standard for Architectural Glazing Materials, Category I and Category II

### **Applications**

Imagine Glass™ can be used for virtually any interior or exterior application (check with Imaging Sciences for specific product applications). Curtain wall, railing systems, furniture, wall systems and elevator cars are just a few examples.

### **Sizes**

The maximum single panel size for Imagine Glass™ in most cases is 60” x 146”. Photographic images can be produced in sizes up to 72” x 120” or 50” x any length.

### **Dimensional Tolerances**

Tolerances are based on ASTM C1172-96, Standard Specifications for Laminated Architectural Flat Glass. Length and Width tolerances are cited in section 8.5.1. Tolerances for flatness are in section 8.6.

### **Pattern Matching**

Where the glass is a geometric pattern that requires panel-to-panel matching, as is the case in butt or narrow mullion situations, the standard practice is to start the graphic the same distance from the top of each panel. The tolerances are + or – 3/32 inch from the top edge of the glass. Patterns are centered in rectangles, side-to-side with the same tolerances.

**Cosmetics**

The inspection criteria for Imagine Glass™ are as follows:

<u>Characteristic</u>	<u>Size of 25 SF or less</u>		<u>Size of greater than 25 SF</u>	
	<u>Central</u>	<u>Outer</u>	<u>Central</u>	<u>Outer</u>
Boil	1/16"	3/32"	1/8"	3/16"
Blow In	N/A	CE 1/4"	N/A	CE 1/4"
Fuse	1/32"	1/16"	1/16"	3/32"
Hair Line (Single Strand)	light	medium	light	medium
Dirt Spot	1/16"	3/32"	3/32"	5/32"
Lint Areas (concentrated)	light	light	light	light
Separation	none	none	none	none
Discoloration	none	none	none	none
Short interlayer	N/A	1/4"	N/A	1/4"
Unlaminated chip	N/A	1/4"	N/A	1/4"
Interlayer scuff	light	light	light	light
Interlayer streak	light	light	light	light
Edge ripple (6" length max)	N/A	CE 1/2", EE 3/8"	N/A	CE 1/2", EE 3/8"
Pinholes (1/16" or greater)	none	none	none	none
Mottle or streak	medium	medium	medium	medium
Roll wave distortion	medium	medium	medium	medium

Notes:

- CE is covered edge of glass edge bite.
- EE is exposed edge.
- Central area is an area formed by an oval or circle whose axes or diameters, when centered, do not exceed 80% of the overall dimension.
- Outer area is the area outside the central area.
- Light is light intensity, or defect barely noticeable at 36 inch viewing
- Medium is medium intensity, or defect noticeable at 36 inch viewing but not at 11 feet viewing.